



## Water Feeders – Make-Up

### Series 25-A Make-Up Water Feeder

- For boiler receiver tanks
- Float operated
- Proportional feed action
- Soft seat provides positive seal
- Seal between float chamber and valve chamber is not a positive seal
- Maximum water supply pressure 100 psi (7 kg/cm<sup>2</sup>)
- Maximum inlet water temperature 120°F (49°C)
- Maximum vessel pressure 35 psi (2.5 kg/cm<sup>2</sup>)



Series 25-A



### Dimensions, in. (mm)

| A                                   | B<br>NPT | C                                    | D                                   | E<br>NPT | F          | G                                    | H<br>NPT | J<br>NPT |
|-------------------------------------|----------|--------------------------------------|-------------------------------------|----------|------------|--------------------------------------|----------|----------|
| 1 <sup>3</sup> / <sub>16</sub> (21) | 3/4      | 12 <sup>1</sup> / <sub>4</sub> (311) | 8 <sup>1</sup> / <sub>8</sub> (206) | 1        | 1/2 (12.7) | 10 <sup>3</sup> / <sub>8</sub> (264) | 1        | 3/4      |

### Ordering Information

| Model Number | Part Number | Description          | Weight lbs. (kg) |
|--------------|-------------|----------------------|------------------|
| 25-A         | 126800      | Make-up water feeder | 37.5 (17)        |
| 25-AB        | 126900      | 25-A w/float block   | 41.8 (19)        |

### Capacities

